

AccuPro 5000-PB™ Digital Scale Controller with Push Button Keypad



QUICK SPECS

- Single or dual-channel operation
- 3 Button keypad interface
- High accuracy of ± 0.1 to $\pm 0.25\%$ of capacity
- Alphanumeric LCD display with easy readability to 0.1 lb. (kg)
- Readout in pounds, kilograms, gallons or liters
- 4-20 mA outputs and optional set point relays
- For use with Scaleton Cylinder, Ton Cylinder, Drum, Tank, Platform, IBC Tote and Spill Containment Scale Bases

Advanced Digital Scale Controller with 1 or 2 Channels Offers Tare Knob Interface

The Model AccuPro 5000-EK Digital Scale Controller is designed for use with Scaleton's complete line of cylinder, ton cylinder, drum, tank, platform, IBC tote and spill containment scale bases. Featuring an easy to read alphanumeric LCD display and push button keypad, the controller provides an excellent accuracy of $\pm 0.1\%$ to $\pm 0.25\%$ of full scale capacity and will display net weight or gross weight in pounds or kilograms. This controller is available with 1 or 2 channels with 4-20 mA outputs and an audible alarm. The 4-20mA output (scale or loop powered) is scalable to a user defined value, and is adjustable. Options include high and low set point relay contacts and 0-5V or 0-10V outputs. The user may apply the indicator to filling applications, as well as loading applications.

Standard Features

- Electronic indicator housed in NEMA 4X, UL approved enclosure to provide protection from acids
- Single or dual channel operation
- Keypad with three (3) push buttons
- 4-20 mA analog output for each channel
- Leak detector input
- Audible alert/alarm with adjustable volume
- Compatibility with all Scaleton scales
- Ability to mix different scale types on one controller
- Multi-level menu system for ease of operation
- Tare lock-out and password protection
- Field programmable and calibratable including factory restore setting
- 6 Foot power cord

Options

- High and low level set point relay contacts – 2 or 4 per channel
- 0-5V or 0-10V output signal
- Remote mounting of indicator box up to 200 feet (61 meters) away from scale base

Model AccuPro 5000-PB™ Digital Scale Controller with Keypad Specifications

PART NUMBER	ACCUPRO 5000-PB
Interface	Keypad with three (3) push buttons
Accuracy	±0.1% to ±0.25% of full scale capacity
Display	6 Digit alphanumeric backlit LCD
Display Units	Pounds, kilograms, gallons or liters
Channels	1 or 2 - One scale base per channel
4-20 mA	4-20mA Standard, 0-5V or 0-10V optional – 1 Output per channel, scale or loop powered
Set Points	2 or 4 Relay contacts per channel (high or low)
Remote Option	Can be remotely mounted up to 200 feet from base frame
Audible Alarm	Built-in Piezo buzzer alarm with adjustable volume
Power	120/240 VAC, 50/60 Hz, 0.10/0.05A
Enclosure	NEMA 4X, UL approved enclosure
Shipping Weight	10 lbs.



36 Hudson Rd
Sudbury MA 01776



800-225-4616
www.tisales.com



Scaleton™ Industries, Ltd.
Bedminster Industrial Park
53 Appletree Lane
P.O. Box 365
Plumsteadville, PA 18949 USA

Toll Free: 1-800-257-5911 (USA & Canada)
Phone: (+1) 215-766-2670 (International)
Fax: (+1) 215-766-2672
info@scaletonscales.com