



ITEM #	C	D	E	F	G	H
11862	17-7/8	6	16-1/2	18-1/4	26	1
12442	24	4	22-3/8	24-1/4	32	1-3/8
12462	24	6	22-3/8	24	34	1-3/8
12472	24	7	22-1/2	24-7/16	34	1-3/8
12482	24	8	22-3/8	24-5/8	34	1-3/8
12642	25-3/4	4	24	26-5/8	34	1-3/8
12662	25-3/4	6	24	26-5/8	34	1-3/8
12682	25-3/4	8	24	27	34-1/2	1-3/8
13042	29-3/4	4	27-3/4	30	36	1-1/2
13242	32	4	30-1/4	32	38	1-1/2
13252	31-5/8	4	30	32-1/2	39	1-3/4
13262	31-5/8	6	30	32-1/2	39	1-3/4
13272	32	6-1/2	30	32	43	1-1/2
13282	31-5/8	8	30	32-1/2	39	1-3/4
13642	37-3/4	4	36	38	48	1-1/2
13662	37-3/4	6	36	38	48	1-1/2
13682	37-3/4	8	36	38-3/4	48	1-1/2

**NOTES:**

1. All dimensions are approximate and in inches.
2. Rating: Heavy Duty - Suitable for AASHTO H-20-44 and HS-20-44 highway loading.
3. Material: Gray Iron conforming to ASTM A48 / A48M-03, Class 30B.  
Please specify if required in Class 35B or Ductile Iron.

